

Internet Engineering Task Force (IETF)  
Request for Comments: 8502  
Category: Standards Track  
ISSN: 2070-1721

Z. Zhang  
Juniper Networks, Inc.  
H. Tsunoda  
Tohoku Institute of Technology  
December 2018

## L2L3 VPN Multicast MIB

### Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes two MIB modules that will be used by other MIB modules for monitoring and/or configuring Layer 2 and Layer 3 Virtual Private Networks that support multicast.

### Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 7841.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <https://www.rfc-editor.org/info/rfc8502>.

### Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	2
1.1. Terminology . . . . .	3
2. The Internet-Standard Management Framework . . . . .	4
3. Summary of MIB Modules . . . . .	4
4. Definitions . . . . .	4
4.1. L2L3-VPN-MULTICAST-TC-MIB Object Definitions . . . . .	4
4.2. L2L3-VPN-MULTICAST-MIB Object Definitions . . . . .	9
5. Security Considerations . . . . .	15
6. IANA Considerations . . . . .	16
7. References . . . . .	17
7.1. Normative References . . . . .	17
7.2. Informative References . . . . .	19
Acknowledgements . . . . .	20
Authors' Addresses . . . . .	20

## 1. Introduction

In BGP/MPLS Virtual Private Networks (VPNs), the Border Gateway Protocol (BGP) is used for distributing routes and Multiprotocol Label Switching (MPLS) is used for forwarding packets across service provider networks.

The procedures for supporting multicast in a BGP/MPLS Layer 3 (L3) VPN are specified in [RFC6513]. The procedures for supporting multicast in a BGP/MPLS Layer 2 (L2) VPN are specified in [RFC7117]. Throughout this document, we will use the term "L2L3VpnMcast network" to mean a BGP/MPLS L2 and L3 VPN that supports multicast.

L2L3VpnMcast networks use various transport mechanisms for forwarding a packet to all or a subset of Provider Edge (PE) routers across service provider networks. These transport mechanisms are abstracted as provider tunnels (P-tunnels). The type of P-tunnel indicates the type of tunneling technology used to establish the P-tunnel. The syntax and semantics of a Tunnel Identifier are determined by the corresponding P-tunnel type [RFC6514]. The P-tunnel type and P-tunnel identifier together identify a P-tunnel.

A BGP attribute that specifies information of a P-tunnel is called a Provider Multicast Service Interface (PMSI) Tunnel attribute. The PMSI Tunnel attribute is advertised/received by PEs in BGP auto-discovery (A-D) routes. [RFC6514] defines the format of a PMSI Tunnel attribute. The P-tunnel type and the P-tunnel identifier are included in the corresponding PMSI Tunnel attribute.

This document describes textual conventions (TCs) and common managed objects (MOs) that will be used by other Management Information Base (MIB) modules for monitoring and/or configuring L2L3VpnMCast networks.

This document defines two TCs to represent

- (a) the type of a P-tunnel and
- (b) the identifier of a P-tunnel

The document also defines MOs that will provide the information contained in a PMSI Tunnel attribute and corresponding P-tunnel.

### 1.1. Terminology

This document adopts the definitions, acronyms, and mechanisms described in [RFC6513] [RFC6514] [RFC7117] and other documents that they refer to. Familiarity with multicast, MPLS, Layer 3 VPN, and Multicast VPN concepts and/or mechanisms is assumed. Some terms specifically related to this document are explained below.

PMSI [RFC6513] is a conceptual interface instantiated by a P-tunnel, which is a transport mechanism used to deliver multicast traffic. A PE uses it to send customer multicast traffic to all or some PEs in the same VPN.

There are two kinds of PMSIs: Inclusive PMSI (I-PMSI) and Selective PMSI (S-PMSI) [RFC6513]. An I-PMSI is a PMSI that enables a PE attached to a particular Multicast VPN to transmit a message to all PEs in the same VPN. An S-PMSI is a PMSI that enables a PE attached to a particular Multicast VPN to transmit a message to some of the PEs in the same VPN.

Throughout this document, we will use the term "PMSI" to refer to both "I-PMSI" and "S-PMSI".

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

## 2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

## 3. Summary of MIB Modules

This document defines two MIB modules: L2L3-VPN-MULTICAST-TC-MIB and L2L3-VPN-MULTICAST-MIB.

- o L2L3-VPN-MULTICAST-TC-MIB contains two textual conventions: L2L3VpnMcastProviderTunnelType and L2L3VpnMcastProviderTunnelId. L2L3VpnMcastProviderTunnelType provides an enumeration of the P-tunnel types. L2L3VpnMcastProviderTunnelId represents an identifier of a P-tunnel.
- o L2L3-VPN-MULTICAST-MIB defines the following table: L2L3VpnMcastPmsiTunnelAttributeTable. An entry in this table corresponds to the attribute information of a specific P-tunnel on a PE router. Entries in this table will be used by other MIB modules for monitoring and/or configuring an L2L3VpnMcast network. The table index uniquely identifies a P-tunnel. It is composed of a type and identifier of a P-tunnel. The table may also be used in conjunction with other MIBs, such as the MPLS Traffic Engineering MIB (MPLS-TE-STD-MIB) [RFC3812], to obtain further information about a P-tunnel. It may also be used in conjunction with the Interfaces Group MIB (IF-MIB) [RFC2863] to obtain further information about the interface corresponding to a P-tunnel.

## 4. Definitions

### 4.1. L2L3-VPN-MULTICAST-TC-MIB Object Definitions

This MIB module makes reference to the following documents: [RFC4875], [RFC5015], [RFC6388], [RFC7524], and [RFC7761].

```
L2L3-VPN-MULTICAST-TC-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
  MODULE-IDENTITY, mib-2
    FROM SNMPv2-SMI -- RFC 2578
```

```
  TEXTUAL-CONVENTION
    FROM SNMPv2-TC; -- RFC 2579
```

```
L2L3VpnMcastTCMIB MODULE-IDENTITY
```

```
  LAST-UPDATED "201812140000Z" -- 14 December 2018
```

```
  ORGANIZATION "IETF BESS Working Group"
```

```
  CONTACT-INFO
```

```
    "Zhaohui Zhang
     Juniper Networks, Inc.
     10 Technology Park Drive
     Westford, MA 01886
     United States of America
     Email: zzhang@juniper.net
```

```
    Hiroshi Tsunoda
     Tohoku Institute of Technology
     35-1, Yagiyama Kasumi-cho
     Taihaku-ku, Sendai, 982-8577
     Japan
     Email: tsuno@m.ieice.org"
```

```
DESCRIPTION
```

```
"This MIB module specifies textual conventions for
Border Gateway Protocol/Multiprotocol Label
Switching Layer 2 and Layer 3 Virtual Private Networks
that support multicast (L2L3VpnMCast networks).
```

```
Copyright (c) 2018 IETF Trust and the persons identified
as authors of the code. All rights reserved.
```

```
Redistribution and use in source and binary forms, with or
without modification, is permitted pursuant to, and subject
to the license terms contained in, the Simplified BSD
License set forth in Section 4.c of the IETF Trust's Legal
Provisions Relating to IETF Documents
(http://trustee.ietf.org/license-info).
```

```
"
```

-- Revision History

REVISION "201812140000Z" -- 14 December 2018

DESCRIPTION

"Initial version, published as RFC 8502."

::= { mib-2 244 }

-- Textual Convention

L2L3VpnMcastProviderTunnelType ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"This textual convention enumerates values representing the type of a provider tunnel (P-tunnel) used for L2L3VpnMCast networks. These labeled numbers are aligned with the definition of Tunnel Types in Section 5 of RFC 6514 and Section 14.1 of RFC 7524.

The enumerated values and the corresponding P-tunnel types are as follows:

noTunnelInfo	(0)	: No tunnel information	RFC 6514
rsvpP2mp	(1)	: RSVP-TE P2MP LSP	RFC 4875
ldpP2mp	(2)	: mLDP P2MP LSP	RFC 6388
pimSsm	(3)	: PIM-SSM Tree	RFC 7761
pimAsm	(4)	: PIM-SM Tree	RFC 7761
pimBidir	(5)	: BIDIR-PIM Tree	RFC 5015
ingressReplication	(6)	: Ingress Replication	RFC 6513
ldpMp2mp	(7)	: mLDP MP2MP LSP	RFC 6388
transportTunnel	(8)	: Transport Tunnel	RFC 7524

These numbers are registered at IANA.  
A current list of assignments can be found at  
<<https://www.iana.org/assignments/bgp-parameters/>>.

"

REFERENCE

"RFC 4875  
RFC 5015  
RFC 6388  
RFC 6513  
RFC 6514, Section 5  
RFC 7524, Section 14.1  
RFC 7761

"

```

SYNTAX          INTEGER
{
    noTunnelInfo      (0),
    rsvpP2mp          (1),
    ldpP2mp           (2),
    pimSsm            (3),
    pimAsm            (4),
    pimBidir          (5),
    ingressReplication (6),
    ldpMp2mp          (7),
    transportTunnel   (8)
}

```

L2L3VpnMcastProviderTunnelId ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"This textual convention represents the Tunnel Identifier of a P-tunnel.

The size of the identifier depends on the address family (IPv4 or IPv6) and the value of the corresponding L2L3VpnMcastProviderTunnelType object.

The corresponding L2L3VpnMcastProviderTunnelType object represents the type of tunneling technology used to establish the P-tunnel.

The size of the identifier for each tunneling technology is summarized below.

L2L3VpnMcastProviderTunnelType (tunneling technology)		Size (in octets)	
		IPv4	IPv6
noTunnelInfo	(No tunnel information)	0	0
rsvpP2mp	(RSVP-TE P2MP LSP)	12	24
ldpP2mp	(mLDP P2MP LSP)	17	29
pimSsm	(PIM-SSM Tree)	8	32
pimAsm	(PIM-SM Tree)	8	32
pimBidir	(BIDIR-PIM Tree)	8	32
ingressReplication	(Ingress Replication)	4	16
ldpMp2mp	(mLDP MP2MP LSP)	17	29
transportTunnel	(Transport Tunnel)	8	32

The Tunnel Type is set to 'No tunnel information' when the PMSI Tunnel attribute carries no tunnel information (there is no Tunnel Identifier). The value of the corresponding L2L3VpnMcastProviderTunnelId object will be a string of length zero.

For Tunnel Type `rsvpP2mp(1)`, the corresponding Tunnel Identifier is composed of an Extended Tunnel ID (4 octets in IPv4, 16 octets in IPv6), 2 unused (Reserved) octets that of value zero, a Tunnel ID (2 octets), and a Point-to-Multipoint (P2MP) ID (4 octets). The size of the corresponding `L2L3VpnMcastProviderTunnelId` object will be 12 octets in IPv4 and 24 octets in IPv6.

For Tunnel Type `ldpP2mp(2)`, the corresponding Tunnel Identifier is the P2MP Forwarding Equivalence Class (FEC) Element (RFC 6388). The size of the corresponding `L2L3VpnMcastProviderTunnelId` object will be 17 octets in IPv4 and 29 octets in IPv6.

For Tunnel Types `pimSsm(3)`, `PimAsm(4)`, and `PimBidir(5)`, the corresponding Tunnel Identifier is composed of the source IP address and the group IP address. The size of the corresponding `L2L3VpnMcastProviderTunnelId` object will be 8 octets in IPv4 and 32 octets in IPv6.

For Tunnel Type `ingressReplication(6)`, the Tunnel Identifier is the unicast tunnel endpoint IP address of the local PE. The size of the corresponding `L2L3VpnMcastProviderTunnelId` object will be 4 octets in IPv4 and 16 octets in IPv6.

For Tunnel Type `ldpMp2mp(7)`, the Tunnel Identifier is a Multipoint-to-Multipoint (MP2MP) FEC Element (RFC 6388). The size of the corresponding `L2L3VpnMcastProviderTunnelId` object will be 17 octets in IPv4 and 29 octets in IPv6.

For Tunnel Type `transportTunnel(8)`, the Tunnel Identifier is a tuple of Source PE Address and Local Number, which is a number that is unique to the Source PE (RFC 7524). Both Source PE Address and Local Number are 4 octets in IPv4 and 16 octets in IPv6. The size of the corresponding `L2L3VpnMcastProviderTunnelId` object will be 8 octets in IPv4 and 32 octets in IPv6.

"

#### REFERENCE

"RFC 6514, Section 5  
 RFC 4875, Section 19.1  
 RFC 6388, Sections 2.2 and 3.2  
 RFC 7524, Section 14.1

"

SYNTAX            OCTET STRING ( SIZE (0|4|8|12|16|17|24|29|32) )

END



## 4.2. L2L3-VPN-MULTICAST-MIB Object Definitions

This MIB module makes reference to the following documents:  
[RFC3811].

L2L3-VPN-MULTICAST-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY, OBJECT-TYPE, mib-2, zeroDotZero  
FROM SNMPv2-SMI -- RFC 2578

MODULE-COMPLIANCE, OBJECT-GROUP  
FROM SNMPv2-CONF -- RFC 2580

RowPointer  
FROM SNMPv2-TC -- RFC 2579

MplsLabel  
FROM MPLS-TC-STD-MIB -- RFC 3811

L2L3VpnMcastProviderTunnelType,  
L2L3VpnMcastProviderTunnelId  
FROM L2L3-VPN-MULTICAST-TC-MIB; -- RFC 8502

L2L3VpnMcastMIB MODULE-IDENTITY

LAST-UPDATED "201812140000Z" -- 14 December 2018

ORGANIZATION "IETF BESS Working Group"

CONTACT-INFO

"Zhaohui Zhang  
Juniper Networks, Inc.  
10 Technology Park Drive  
Westford, MA 01886  
United States of America  
Email: zzhang@juniper.net

Hiroshi Tsunoda  
Tohoku Institute of Technology  
35-1, Yagiyama Kasumi-cho  
Taihaku-ku, Sendai, 982-8577  
Japan  
Email: tsuno@m.ieice.org"

DESCRIPTION

"This MIB module defines a table representing the attribute information of the provider tunnels (P-tunnels) on a PE router. This MIB module will be used by other MIB modules designed for monitoring and/or configuring Border Gateway Protocol/Multiprotocol Label Switching

Layer 2 and Layer 3 Virtual Private  
Network that support multicast (L2L3VpnMCast network).

Copyright (c) 2018 IETF Trust and the persons identified  
as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or  
without modification, is permitted pursuant to, and subject  
to the license terms contained in, the Simplified BSD License  
set forth in Section 4.c of the IETF Trust's Legal Provisions  
Relating to IETF Documents  
(<http://trustee.ietf.org/license-info>).

"

-- Revision History

REVISION "201812140000Z" -- 14 December 2018  
DESCRIPTION  
"Initial version, published as RFC 8502."

::= { mib-2 245 }

-- Top-level components of this MIB.

l2L3VpnMcastStates OBJECT IDENTIFIER  
 ::= { l2L3VpnMcastMIB 1 }

l2L3VpnMcastConformance OBJECT IDENTIFIER  
 ::= { l2L3VpnMcastMIB 2 }

-- Tables, Scalars, Conformance Information

-- Table of PMSI Tunnel Attributes

l2L3VpnMcastPmsiTunnelAttributeTable OBJECT-TYPE  
SYNTAX SEQUENCE OF L2L3VpnMcastPmsiTunnelAttributeEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION

"An entry in this table corresponds to  
the attribute information of a specific  
P-tunnel on a PE router.  
A part of the attributes corresponds to fields in  
a Provider Multicast Service Interface (PMSI) Tunnel  
attribute advertised and received by a PE router.  
The entries will be referred to by other MIB modules  
for monitoring and/or configuring L2L3VpnMCast networks.

"

## REFERENCE

"RFC 6514, Section 5"

::= { l2L3VpnMcastStates 1 }

l2L3VpnMcastPmsiTunnelAttributeEntry OBJECT-TYPE  
 SYNTAX L2L3VpnMcastPmsiTunnelAttributeEntry  
 MAX-ACCESS not-accessible  
 STATUS current  
 DESCRIPTION

"A conceptual row corresponding to a specific  
 P-tunnel on this router.  
 "

## REFERENCE

"RFC 6514, Section 5"

INDEX {  
     l2L3VpnMcastPmsiTunnelAttributeType,  
     l2L3VpnMcastPmsiTunnelAttributeId  
 }  
 ::= { l2L3VpnMcastPmsiTunnelAttributeTable 1 }

l2L3VpnMcastPmsiTunnelAttributeEntry ::=

```
SEQUENCE {
    l2L3VpnMcastPmsiTunnelAttributeType
        l2L3VpnMcastProviderTunnelType,
    l2L3VpnMcastPmsiTunnelAttributeId
        l2L3VpnMcastProviderTunnelId,
    l2L3VpnMcastPmsiTunnelLeafInfoRequired
        INTEGER,
    l2L3VpnMcastPmsiTunnelAttributeMplsLabel
        MplsLabel,
    l2L3VpnMcastPmsiTunnelPointer
        RowPointer,
    l2L3VpnMcastPmsiTunnelIf
        RowPointer
}
```

l2L3VpnMcastPmsiTunnelAttributeType OBJECT-TYPE  
 SYNTAX L2L3VpnMcastProviderTunnelType  
 MAX-ACCESS not-accessible  
 STATUS current  
 DESCRIPTION  
 "This object indicates the type of tunneling technology  
 used to establish the P-tunnel corresponding to this entry.  
  
 When BGP-based PMSI signaling is used, the value of  
 this object corresponds to the Tunnel Type field  
 in the PMSI Tunnel attribute advertised/received  
 in a PMSI auto-discovery (A-D) route.

```

"
REFERENCE
  "RFC 6514, Section 5"
 ::= { l2L3VpnMcastPmsiTunnelAttributeEntry 1 }

```

```

l2L3VpnMcastPmsiTunnelAttributeId OBJECT-TYPE
SYNTAX      L2L3VpnMcastProviderTunnelId
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
  "This object represents the Tunnel Identifier field, which
   uniquely identifies a P-tunnel, in the PMSI Tunnel attribute
   of the P-tunnel corresponding to this entry.

   The size of the identifier depends on the address family
   (IPv4 or IPv6) and the value of the corresponding
   l2L3VpnMcastPmsiTunnelAttributeType object, i.e., the type of
   tunneling technology used to establish the P-tunnel.
"

```

```

REFERENCE
  "RFC 6514, Section 5"
 ::= { l2L3VpnMcastPmsiTunnelAttributeEntry 2 }

```

```

l2L3VpnMcastPmsiTunnelLeafInfoRequired OBJECT-TYPE
SYNTAX      INTEGER {
                false      (0),
                true        (1),
                notAvailable (2)
            }
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
  "When the value of this object is set to 1 (true),
   it indicates that the PE that originated the
   PMSI Tunnel attribute of the P-tunnel corresponding
   to this entry requests receivers to originate
   a new Leaf A-D route.

   A value of zero (false) indicates that there is no such
   request.

   When the P-tunnel does not have a corresponding PMSI
   Tunnel attribute, the value of this object will be
   2 (notAvailable).
"

```

In the case of multicast in MPLS/BGP IP VPNs, this object represents the 'Leaf Information Required flag' (RFC 6514) in the Flags field in the PMSI Tunnel attribute of the P-tunnel corresponding to this entry.

"

## REFERENCE

"RFC 6514, Section 5

"

::= { l2L3VpnMcastPmsiTunnelAttributeEntry 3 }

## l2L3VpnMcastPmsiTunnelAttributeMplsLabel OBJECT-TYPE

SYNTAX MplsLabel

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"This object represents the MPLS Label in the PMSI Tunnel attribute of the P-tunnel corresponding to this entry.

When BGP-based PMSI signaling is used, the PMSI Tunnel attribute of the P-tunnel will be advertised/received in a PMSI A-D route. The value of this object corresponds to the MPLS Label in the attribute.

When the P-tunnel does not have a PMSI tunnel attribute, the value of this object will be zero.

"

## REFERENCE

"RFC 6514, Section 5"

::= { l2L3VpnMcastPmsiTunnelAttributeEntry 4 }

## l2L3VpnMcastPmsiTunnelPointer OBJECT-TYPE

SYNTAX RowPointer

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"Details of a P-tunnel identified by l2L3VpnMcastPmsiTunnelAttributeId may be present in some other table, e.g., mplsTunnelTable (RFC 3812). This object specifies the pointer to the row that pertains to the entry in the table.

If no such entry exists, the value of this object will be zeroDotZero.

"

## REFERENCE

"RFC 3812, Sections 6.1 and 11"

DEFVAL { zeroDotZero }

```

 ::= { 12L3VpnMcastPmsiTunnelAttributeEntry 5 }

12L3VpnMcastPmsiTunnelIf OBJECT-TYPE
    SYNTAX          RowPointer
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "If the P-tunnel identified by
         12L3VpnMcastPmsiTunnelAttributeId has a corresponding
         entry in ifXTable (RFC 2863), this object will
         point to the row in ifXTable that pertains to the entry.
         Otherwise, the value of this object will be zeroDotZero.
        "
    REFERENCE
        "RFC 2863, Section 6"
    DEFVAL          { zeroDotZero }
    ::= { 12L3VpnMcastPmsiTunnelAttributeEntry 6 }

-- Conformance Information

12L3VpnMcastCompliances OBJECT IDENTIFIER
    ::= { 12L3VpnMcastConformance 1 }
12L3VpnMcastGroups      OBJECT IDENTIFIER
    ::= { 12L3VpnMcastConformance 2 }

-- Compliance Statements

12L3VpnMcastCoreCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The core compliance statement for SNMP entities
         that implement the L2L3-VPN-MULTICAST-MIB module.
        "
    MODULE -- this module

    MANDATORY-GROUPS {
        12L3VpnMcastCoreGroup
    }
    ::= { 12L3VpnMcastCompliances 1 }

12L3VpnMcastFullCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The full compliance statement for SNMP entities
         that implement the L2L3-VPN-MULTICAST-MIB module.
        "
    MODULE -- this module

```

```

MANDATORY-GROUPS {
    12L3VpnMcastCoreGroup,
    12L3VpnMcastOptionalGroup
}
::= { 12L3VpnMcastCompliances 2 }

-- Units of Conformance

12L3VpnMcastCoreGroup    OBJECT-GROUP
OBJECTS {
    12L3VpnMcastPmsiTunnelLeafInfoRequired,
    12L3VpnMcastPmsiTunnelAttributeMplsLabel
}
STATUS          current
DESCRIPTION
    "Support of these objects is required.
    "
::= { 12L3VpnMcastGroups 1 }

12L3VpnMcastOptionalGroup    OBJECT-GROUP
OBJECTS {
    12L3VpnMcastPmsiTunnelPointer,
    12L3VpnMcastPmsiTunnelIf
}
STATUS          current
DESCRIPTION
    "Support of these objects is optional.
    "
::= { 12L3VpnMcastGroups 2 }

END

```

## 5. Security Considerations

There are no management objects defined in these MIB modules that have a MAX-ACCESS clause of read-write and/or read-create. So, if this MIB module is implemented correctly, then there is no risk that an intruder can alter or create any management objects of this MIB module via direct SNMP SET operations.

Some of the objects in these MIB modules may be considered sensitive or vulnerable in some network environments. This includes INDEX objects with a MAX-ACCESS of not-accessible, and any indices from other modules exposed via AUGMENTS. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

- o the `l2L3VpnMcastPmsiTunnelAttributeTable` collectively shows the P-tunnel network topology and its performance characteristics. For instance, `l2L3VpnMcastPmsiTunnelAttributeId` in this table will contain the identifier that uniquely identifies a P-tunnel. This identifier may be composed of source and multicast group IP addresses. `l2L3VpnMcastPmsiTunnelPointer` and `l2L3VpnMcastPmsiTunnelIf` will point to the corresponding entries in other tables containing configuration and/or performance information of a P-tunnel and its interface. If an Administrator does not want to reveal this information, then these objects should be considered sensitive/vulnerable.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

Implementations SHOULD provide the security features described by the SNMPv3 framework (see [RFC3410]), and implementations claiming compliance to the SNMPv3 standard MUST include full support for authentication and privacy via the User-based Security Model (USM) [RFC3414] with the AES cipher algorithm [RFC3826]. Implementations MAY also provide support for the Transport Security Model (TSM) [RFC5591] in combination with a secure transport such as SSH [RFC5592] or TLS/DTLS [RFC6353].

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

## 6. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the "SMI Network Management MGMT Codes Internet-standard MIB" registry:

Name	Description	OBJECT-IDENTIFIER value
<code>l2L3VpnMcastTCMIB</code>	<code>L2L3-VPN-MULTICAST-TC-MIB</code>	{ mib-2 244 }
<code>l2L3VpnMcastMIB</code>	<code>L2L3-VPN-MULTICAST-MIB</code>	{ mib-2 245 }



## 7. References

### 7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, DOI 10.17487/RFC2578, April 1999, <<https://www.rfc-editor.org/info/rfc2578>>.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, RFC 2579, DOI 10.17487/RFC2579, April 1999, <<https://www.rfc-editor.org/info/rfc2579>>.
- [RFC2580] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Conformance Statements for SMIv2", STD 58, RFC 2580, DOI 10.17487/RFC2580, April 1999, <<https://www.rfc-editor.org/info/rfc2580>>.
- [RFC2863] McCloghrie, K. and F. Kastenholtz, "The Interfaces Group MIB", RFC 2863, DOI 10.17487/RFC2863, June 2000, <<https://www.rfc-editor.org/info/rfc2863>>.
- [RFC3414] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", STD 62, RFC 3414, DOI 10.17487/RFC3414, December 2002, <<https://www.rfc-editor.org/info/rfc3414>>.
- [RFC3811] Nadeau, T., Ed. and J. Cucchiara, Ed., "Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management", RFC 3811, DOI 10.17487/RFC3811, June 2004, <<https://www.rfc-editor.org/info/rfc3811>>.
- [RFC3812] Srinivasan, C., Viswanathan, A., and T. Nadeau, "Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)", RFC 3812, DOI 10.17487/RFC3812, June 2004, <<https://www.rfc-editor.org/info/rfc3812>>.

- [RFC3826] Blumenthal, U., Maino, F., and K. McCloghrie, "The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model", RFC 3826, DOI 10.17487/RFC3826, June 2004, <<https://www.rfc-editor.org/info/rfc3826>>.
- [RFC4875] Aggarwal, R., Ed., Papadimitriou, D., Ed., and S. Yasukawa, Ed., "Extensions to Resource Reservation Protocol - Traffic Engineering (RSVP-TE) for Point-to-Multipoint TE Label Switched Paths (LSPs)", RFC 4875, DOI 10.17487/RFC4875, May 2007, <<https://www.rfc-editor.org/info/rfc4875>>.
- [RFC5015] Handley, M., Kouvelas, I., Speakman, T., and L. Vicisano, "Bidirectional Protocol Independent Multicast (BIDIR-PIM)", RFC 5015, DOI 10.17487/RFC5015, October 2007, <<https://www.rfc-editor.org/info/rfc5015>>.
- [RFC5591] Harrington, D. and W. Hardaker, "Transport Security Model for the Simple Network Management Protocol (SNMP)", STD 78, RFC 5591, DOI 10.17487/RFC5591, June 2009, <<https://www.rfc-editor.org/info/rfc5591>>.
- [RFC5592] Harrington, D., Salowey, J., and W. Hardaker, "Secure Shell Transport Model for the Simple Network Management Protocol (SNMP)", RFC 5592, DOI 10.17487/RFC5592, June 2009, <<https://www.rfc-editor.org/info/rfc5592>>.
- [RFC6353] Hardaker, W., "Transport Layer Security (TLS) Transport Model for the Simple Network Management Protocol (SNMP)", STD 78, RFC 6353, DOI 10.17487/RFC6353, July 2011, <<https://www.rfc-editor.org/info/rfc6353>>.
- [RFC6388] Wijnands, IJ., Ed., Minei, I., Ed., Kompella, K., and B. Thomas, "Label Distribution Protocol Extensions for Point- to-Multipoint and Multipoint-to-Multipoint Label Switched Paths", RFC 6388, DOI 10.17487/RFC6388, November 2011, <<https://www.rfc-editor.org/info/rfc6388>>.
- [RFC6513] Rosen, E., Ed. and R. Aggarwal, Ed., "Multicast in MPLS/BGP IP VPNs", RFC 6513, DOI 10.17487/RFC6513, February 2012, <<https://www.rfc-editor.org/info/rfc6513>>.
- [RFC6514] Aggarwal, R., Rosen, E., Morin, T., and Y. Rekhter, "BGP Encodings and Procedures for Multicast in MPLS/BGP IP VPNs", RFC 6514, DOI 10.17487/RFC6514, February 2012, <<https://www.rfc-editor.org/info/rfc6514>>.

- [RFC7117] Aggarwal, R., Ed., Kamite, Y., Fang, L., Rekhter, Y., and C. Kodeboniya, "Multicast in Virtual Private LAN Service (VPLS)", RFC 7117, DOI 10.17487/RFC7117, February 2014, <<https://www.rfc-editor.org/info/rfc7117>>.
- [RFC7524] Rekhter, Y., Rosen, E., Aggarwal, R., Morin, T., Grosclaude, I., Leymann, N., and S. Saad, "Inter-Area Point-to-Multipoint (P2MP) Segmented Label Switched Paths (LSPs)", RFC 7524, DOI 10.17487/RFC7524, May 2015, <<https://www.rfc-editor.org/info/rfc7524>>.
- [RFC7761] Fenner, B., Handley, M., Holbrook, H., Kouvelas, I., Parekh, R., Zhang, Z., and L. Zheng, "Protocol Independent Multicast - Sparse Mode (PIM-SM): Protocol Specification (Revised)", STD 83, RFC 7761, DOI 10.17487/RFC7761, March 2016, <<https://www.rfc-editor.org/info/rfc7761>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

## 7.2. Informative References

- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, DOI 10.17487/RFC3410, December 2002, <<https://www.rfc-editor.org/info/rfc3410>>.

## Acknowledgements

Glenn Mansfield Keeni did the MIB Doctor review and provided valuable comments.

## Authors' Addresses

Zhaohui (Jeffrey) Zhang  
Juniper Networks, Inc.  
10 Technology Park Drive  
Westford, MA 01886  
United States of America

Email: [zzhang@juniper.net](mailto:zzhang@juniper.net)

Hiroshi Tsunoda  
Tohoku Institute of Technology  
35-1, Yagiyama Kasumi-cho  
Taihaku-ku, Sendai 982-8577  
Japan

Phone: +81-22-305-3411  
Email: [tsuno@m.ieice.org](mailto:tsuno@m.ieice.org)